



QUALITY CERTIFICATE

2 PCS. FULL BORE BALL VALVE Ref. 2528

MATERIAL:

2 PCS. FULL BORE BALL VALVE FIRE-SAFE DESIGN
DIRECT MOUNTING FOR ACTUATORS ACCORDING ISO 5211
CONSTRUCTION MADE OF STAINLESS STEEL CF8M, S.S. 316
FLANGES DIN PN40, FOR DN50 OR LOWER
FLANGES DIN PN16, FOR HIGHER THAN DN 50
MANUAL OPERATED BY HANDLE
SEATS: PTFE + 15% GLASS FIBER
O-RING STEM: VITON

CHARACTERISTICS:

NOMINAL PRESSURE: 16 kg/cm² DN>50
NOMINAL PRESSURE: 40 kg/cm² DN<50 OR DN=50
MAX. WORKING TEMP.: +180 °C
MIN. WORKING TEMP.: - 30 °C

OTHER CHARACTERISTICS:

VALVE IS SUITABLE TO WORK IN LOW VACUUM FROM ATMOSPHERIC PRESSURE TO 500 mbar OF ABSOLUTE PRESSURE.

WE HEREBY CERTIFICATE:

WE HEREBY CERTIFICATE THAT THE MATERIAL DESCRIBED HAS BEEN MADE AND TESTED IN ACORDANCE WITH THE SPECIFICATION.